

# GLORIA®

Safety First






## Foam Fire Extinguisher SD 6/9 E





### ■ Main advantages of the SD 6/9 E

- Available in 6 l and 9 l version
- Ready for immediate use after the safety pin is pulled out
- Practical devices of standard class of high extinguishing performance
- Easy to use squeeze-grip operation - for carrying and releasing at the same time
- Extinguishing agent container made of high-quality steel
- Hose assembly resistant to aging

### ■ Details and performance features of the SD 6/9 E

- External weather-resistant and durable coating
- Holder for extinguishing nozzle integrated into skirt
- Durable brass fitting with integrated test valve
- With wall bracket
- Suitable for electrical installations up to 1000 volts at a minimum distance of 1 m
- Foam with impregnating effect on the source of the fire and surroundings
- Special foam nozzle with high surface coverage enables optimum application of the extinguishing agent
- Reignition is largely suppressed.
- Areas of application:     

Type	Art.-No.	Extinguishing agent	Model	Propellant	Performance LE*	Discharge time/-range	Temperature range	Total weight	H/W/D in bracket ø - cylinder
 SD 6 E	814222.1808	Premix	S 6 L	N <sub>2</sub>	21A 144B 6 9	ca. 4 m ca. 35 Sec.	5 °C to +60 °C	ca. 10,5 kg	ca. 557/275/165 mm ø 150 mm
 SD 9 E	814232.1808	Premix	S 9 L	N <sub>2</sub>	27A 183B 9 12	ca. 4 m ca. 48 Sec.	5 °C to +60 °C	ca. 14,6 kg	ca. 617/300/202 mm ø 190 mm

\* Extinguishing agent units. If fire extinguishers are intended for both fire classes A+B, the lower LE value applies for the calculation.