

GLORIA®

Safety First

Foam Fire Extinguisher SDB 6/9 P



GLORIA

Safety First

GLORIA GmbH | Diestedder Straße 39 | 59329 Wadersloh
Telefon +49 (0)2523 79349-900 | Telefax +49 (0)2523 79349-93
info@gloria.de | www.gloria.de

■ Main advantages of the SDB 6/9 P

- Available in 6 l and 9 l version
- Ready for immediate use after the safety pin is pulled out
- Practical devices of standard class of high extinguishing performance
- Easy to use squeeze-grip operation - for carrying and releasing at the same time
- Extinguishing agent container made of high-quality steel
- Hose assembly resistant to aging

■ Details and performance features of the SDB 6/9 P

- External weather-resistant and durable coating
- Holder for extinguishing nozzle integrated into skirt
- Durable brass fitting with integrated test valve
- With wall bracket
- Suitable for electrical installations up to 1000 volts at a minimum distance of 1 m
- High extinguishing performance (183B) on B-fire (12LE) with only 6 litres capacity.
- Foam with impregnating effect on the source of the fire and the surrounding area
- Special foam nozzle with high surface coverage, enables optimum application of the extinguishing agent.
- Reignition is largely suppressed..
- Areas of application:     

Type	Art.-No.	Extinguishing agent	Model	Propellant	Performance LE*	Discharge time/-range	Temperature range	Total weight	H/W/D in bracket ø - cylinder
 SDB 6 P	813681.0000	Premix	S 6 L	N ₂	21A 6 183B 12	ca. 4 m ca. 42 Sec.	5 °C to +60 °C	ca. 10,5 kg	ca. 540/275/182 mm ø 170 mm
 SDB 9 P	811741.0000	Premix	S 9 L	N ₂	27A 9 183B 12	ca. 4 m ca. 65 Sec.	5 °C to +60 °C	ca. 14,6 kg	ca. 617/300/202 mm ø 190 mm

* Extinguishing agent units. If fire extinguishers are intended for both fire classes A+B, the lower LE value applies for the calculation.