

GLORIA®

Safety First

Foam fire extinguisher SKE 6/9 EASY



Safety First

GLORIA GmbH | Diestedder Straße 39 | 59329 Wadersloh
Telefon +49 (0)2523 79349-900 | Telefax +49 (0)2523 79349-93
info@gloria.de | www.gloria.de

■ Main advantages of SKE EASY

- Available in 6 l and 9 l versions
- Good carrying characteristics due to stable squeeze-grip operation
- Uniform, high-strength, glass-fibre reinforced special plastic valve body. Also robust, tensile strength, stable, high chemical resistance, moisture-resistant, corrosion-free, high temperature resistance, UV-resistant
- All valve components with standardised neck rings
- Uniform neck ring M 74
- Uniform, black anodised metal locking collar
- Age-resistant hose assembly

■ Details and performance features SKE EASY

- Highly maintenance-friendly, no additives in water
- High extinguishing performance on A and B class fires
- Separate storage of foam concentrate in pre-assembled cartridge
- Special foam nozzle with high surface coverage enables ideal application of the extinguishing agent
- Reignition is largely suppressed
- Areas of application:     

■ Cross section SKE 6 EASY

Mode of operation

- Pull the metal safety pin **A**.
- When the **squeeze-grip operation B** is pressed down briefly for the first time, the **piercer C** punctures the **CO₂ propellant gas bottle D**.
- At the same time CO₂ suddenly flows into the **cartridge E** and pushes the foam concentrate into the cylinder. This process ensures that water and foam agent are ideally mixed.
- When the **squeeze-grip operation B** is pressed down again, the extinguishing agent flows through the **rising pipe F** into the **hose assembly G** for discharge.
- By releasing the **squeeze-grip operation B** the extinguishing agent jet is interrupted.



Type	Art.-No.	Extinguishing Agent	Model	Propellant	Extinguishing Performance LE*	Spritzweite Spritzdauer	Temperature range	Total weight	H/B/T with bracket ø – cylinder
 SKE 6 EASY	811681.0000	Foam concentrate in cartridge + water	S 6 H	CO ₂	21A 6 113B 6	ca. 4 m ca. 35 sec	+5 °C to +60 °C	ca. 10,1 kg	ca. 600/310/165 mm 150 mm
 SKE 9 EASY	811691.0000	Foam concentrate in cartridge + water	S 9 H	CO ₂	27A 9 183B 12	ca. 4 m ca. 60 sec	+5 °C to +60 °C	ca. 15,5 kg	ca. 620/290/205 mm 190 mm

* extinguishing agent units. If fire extinguishers are provided for both fire classes A+B, the lower LE value applies for the calculation.