

GLORIA®

Safety First

Powder fire extinguisher P 6/12 PRO



■ **Main advantages of the P PRO**

- Available in 6 kg and 12 kg versions
- Tried-and-tested GLORIA strike-knob activation.
- Robust handle made of glass-fibre reinforced plastic with ergonomic carrying properties.
- Laser-welded pressure cylinder.
- Exterior coated with durable polyester resin powder coating.
- Long-lasting plastic inner coating to protect against corrosion.
- Approved according to Pressure Equipment Directive 2014/68/EU (CE).
- Uniform, high-strength, glass-fibre reinforced special plastic valve body.
- High temperature, ozone and UV resistant.
- In addition, high chemical resistance, moisture-resistant and corrosion-free.
- Uniform neck ring, thread size M74x2.
- Uniform, black anodised metal locking collar
- Internal propellant bottle with stainless steel adapter and corrosion-resistant plastic coating. (technical data marked with resistant laser printing)
- Ageing-resistant, LABS-free quality hose assembly with fabric insert made of synthetic rubber material.
- Rotatable and stoppable extinguishing pistol for ideal fire fighting.
- Robust, impact-resistant plastic skirt with hose nozzle bracket ensures stability and protection of the unit against damage and corrosion.
- Special foam pipe with high area coverage enables optimum application of the extinguishing agent.

■ **Details and performance features of the P PRO**

- Environmentally compatible, performance-differentiated quality ABC extinguishing powder
- Nearly universal application
- Immediate, fast extinguishing due to the effect of cooling and suppression, enriched with an anti-catalytic effect; reignition in the case of fires of solids is suppressed
- The grey colour code indicates a powder extinguishing agent
- GLORIA extinguishing powders are hydrophobic and non-toxic
- GLORIA extinguishing powders with excellent quality and durability
- Areas of application:

Type	Art.-No.	Extinguishing agent	Model	Agent	Performance LE*	Spraying range/-duration	Temperature range	Total weight	H/W/D in bracket ø - cylinder
P 6 PRO	801941.0000	ABC powder	PG 6 H	CO ₂	34A 233B C 10 15	ca. 6 m ca. 22 Sec.	-30 °C to +60 °C	ca. 9,8 kg	ca. 510/300/165 mm ø 150 mm
P 12 PRO	801291.1426	ABC powder	PG 12 H	CO ₂	55A 233B C 15 15	ca. 7 m ca. 32 Sec.	-30 °C to +60 °C	ca. 18,6 kg	ca. 610/290/205 mm ø 190 mm

* extinguishing agent units. If fire extinguishers are provided for both fire classes A+B, the lower LE value applies for the calculation.