

GLORIA®

Safety First

Powder fire extinguisher P 6/12 STAR



■ **Main advantages of the P STAR**

- Available in 6 kg and 12 kg versions
- Intuitive and ready to use in no time: unlock, lift the handle – done!
- Robust carrying handle made of glass-fibre reinforced plastic with ergonomic carrying characteristics.
- Laser-welded pressurised cylinder.
- Exterior coated with durable polyester resin powder coating.
- Long-lasting plastic inner coating to protect against corrosion.
- Approved in accordance with the Pressure Equipment Directive 2014/68/EU (CE).
- Uniform, high-strength, glass fibre-reinforced special plastic valve body.
- High temperature, ozone and UV resistant.
- Also highly resistant to chemicals, moisture and corrosion.
- Standardised neck ring, thread size M74x2.
- Uniform, black anodised metal locking collar.
- Internal propellant bottle with stainless steel adapter and corrosion-resistant plastic coating. (technical data marked with resistant laser printing)
- Ageing-resistant, LABS-free quality hose assembly with fabric insert made of synthetic rubber material.
- Swivelling and adjustable extinguishing pistol for optimum fire fighting.
- Robust, impact-resistant plastic base ring with hose nozzle bracket ensures stability and protects the device against damage and corrosion.
- Special foam tube with high surface coverage enables optimum application of the extinguishing agent.

■ **Details and performance features of the P STAR**

- Environmentally friendly, performance-differentiated quality ABC extinguishing powder
- Nearly universal application
- Immediate, fast extinguishing due to the effect of cooling and suppression, enriched with an anti-catalytic effect
- Reignition of solid fires is prevented
- Gray colour code indicates extinguishing powder
- GLORIA extinguishing powders are hydrophobic and non-toxic
- GLORIA extinguishing powders with excellent quality and durability
- Areas of application:

Type	Art.-No.	Extinguishing agent	Model	Agent	Performance LE*	Spraying range/-duration	Temperature range	Total weight	H/W/D in bracket ø - cylinder
P 6 STAR	800631.0000	ABC powder	PG 6 H	CO ₂	34A 233B 10 15 C	ca. 6 m ca. 22 Sec.	-30 °C to +60 °C	ca. 9,9 kg	ca. 500/300/165 mm ø 150 mm
P 12 STAR	800651.0000	ABC powder	PG 12 H	CO ₂	55A 233B 15 15 C	ca. 7 m ca. 32 Sec.	-30 °C to +60 °C	ca. 18,7 kg	ca. 600/290/205 mm ø 190 mm

* extinguishing agent units. If fire extinguishers are provided for both fire classes A+B, the lower LE value applies for the calculation.