

GLORIA®

Safety First

Foam fire extinguisher SKA+ 6/9 STAR



■ Main advantages of SKA+ STAR

- Available in 6 litre and 9 litre versions
- Special extinguishing agent, free from environmentally harmful PFAS, including PFOA and PFOS
- Special 5-hole fine spray nozzle enables optimum application of the extinguishing agent.
- Intuitive and therefore ready for use in a flash: release the safety catch, simply lift the handle – done!
- Robust carrying handle made of glass fibre reinforced plastic with ergonomic carrying properties.
- Laser-welded pressure vessel.
- Internal propellant bottle with stainless steel adapter and corrosion-resistant plastic coating. (technical data marked with durable laser printing)
- Robust, impact-resistant plastic base ring with hose nozzle holder ensures stability and protects the device against damage and corrosion.
- Age-resistant, LABS-free quality hose with synthetic rubber fabric insert.
- Rotatable and adjustable extinguishing gun for optimum firefighting. Als 6 l und 9 l Version verfügbar
- Special foam pipe with high area coverage enables optimum application of the extinguishing agent.
- Exterior with durable polyester resin powder coating.
- Durable plastic interior coating for protection against corrosion.
- Approved in accordance with Pressure Equipment Directive 2014/68/EU (CE).
- Uniform, high-strength, glass fibre-reinforced special plastic valve body.
- High temperature, ozone and UV resistant.
- Also highly resistant to chemicals, moisture and corrosion.
- Uniform threaded ring, thread size M74x2.
- Uniform, black anodised metal union nut.

■ Details and performance features of the SKA+ STAR 

- High extinguishing performance on A and B fires
- Separate storage of foam concentrate in pre-assembled cartridge and additional water additives.
- Special foam nozzle with high surface coverage enables ideal application of the extinguishing agent
- Reignition is largely suppressed
- Area of application: 

Type	Art.-No.	Extinguishing agent	Model	Agent	Performance LE*	Spraying range/-duration	Temperature range	Total weight	H/W/D in bracket ø - cylinder
 SKA+ 6 STAR	811661.0035	Foam concentrate in cartridge + water + additives	S 6 H	CO ₂	34A 144B 10 9	ca. 4,5 m ca. 60 Sec.	5 °C to +60 °C	ca. 10,1kg	ca. 540/280/165 mm ø 150 mm
 SKA+ 9 STAR	811671.0035	Foam concentrate in cartridge + water + additives	S 9 H	CO ₂	43A 183B 12 12	ca. 4,5 m ca. 80 Sec.	5 °C to +60 °C	ca. 15,3 kg	ca. 575/280/205 mm ø 190 mm

* Löschmitteleinheiten. Sind Feuerlöscher für beide Brandklassen A+B vorgesehen, gilt für die Berechnung der niedrigere LE-Wert.