

# GLORIA®

Safety First

## Foam fire extinguisher SKE 6/9 STAR



**GLORIA®**

**FEUERLÖSCHER  
FIRE EXTINGUISHER**

21 A      6 l Schaum / Foam      113 B

- 1** Sicherungsglasche herausziehen.  
Remove safety Device.
- 2** Gerät am Handgriff anheben.  
Lift extinguisher pulling the d-handle upwards.
- 3** Löschpistole betätigen.  
Press grip of extinguishing pistol.

**A**      **B**

Vorsicht bei elektrischen Anlagen.  
Nur bis 1000 V; Mindestabstand 1 m.  
Attention in presence of electricity!  
Only up to 1000 volts.  
Minimum distance 1 meter.

Hersteller / Manufacturer: Diestedder Str. 39 - D-59329 Wadersloh  
**GLORIA GmbH**      Tel. +49 (0) 25 23 / 793 49 - 900  
www.gloria.de

**■ Main advantages of SKE STAR**

- Available in 6 litre and 9 litre versions
- Special extinguishing agent, free from environmentally harmful PFAS, including PFOA and PFOS
- Special 5-hole fine spray nozzle enables optimum application of the extinguishing agent.
- Intuitive and therefore ready for use in a flash: release the safety catch, simply lift the handle – done!
- Robust carrying handle made of glass fibre reinforced plastic with ergonomic carrying properties.
- Laser-welded pressure vessel.
- Internal propellant bottle with stainless steel adapter and corrosion-resistant plastic coating. (technical data marked with durable laser printing)
- Robust, impact-resistant plastic base ring with hose nozzle holder ensures stability and protects the device against damage and corrosion.
- Age-resistant, LABS-free quality hose with synthetic rubber fabric insert.
- Rotatable and adjustable extinguishing gun for optimum firefighting. Als 6 l und 9 l Version verfügbar
- Special foam pipe with high area coverage enables optimum application of the extinguishing agent.
- Exterior with durable polyester resin powder coating.
- Durable plastic interior coating for protection against corrosion.
- Approved in accordance with Pressure Equipment Directive 2014/68/EU (CE).
- Uniform, high-strength, glass fibre-reinforced special plastic valve body.
- High temperature, ozone and UV resistant.
- Also highly resistant to chemicals, moisture and corrosion.
- Uniform threaded ring, thread size M74x2.
- Uniform, black anodised metal union nut.

**■ Details and performance features of the SKE STAR**

- Highly maintenance-friendly, no additives in the water
- Convincing extinguishing performance on A and B fi res
- Separate storage of foam concentrate in pre-assembled cartridge
- Special foam nozzle with high surface coverage enables ideal application of the extinguishing agent
- Reignition is largely suppressed.
- Areas of application:

Type	Art.-No.	Extinguishing agent	Model	Agent	Performance LE*	Spraying range/-duration	Temperature range	Total weight	H/W/D in bracket ø - cylinder
<b>SKE 6 STAR</b>	811661.0000	Foam concentrate in cartridge + water	S 6 H	CO <sub>2</sub>	21A 113B 6 6	ca. 4,5 m ca. 35 Sec.	5 °C to +60 °C	ca. 10,1 kg	ca. 540/280/165 mm ø 150 mm
<b>SKE 9 STAR</b>	811671.0000	Foam concentrate in cartridge + water	S 9 H	CO <sub>2</sub>	27A 183B 9 12	ca. 4,5 m ca. 60 Sec.	5 °C to +60 °C	ca. 15,3 kg	ca. 575/280/205 mm ø 190 mm

\* extinguishing agent units. If fire extinguishers are provided for both fire classes A+B, the lower LE value applies for the calculation.