

GLORIA®

Safety First

Foam fire extinguisher SB 6/9 PRO



■ **Main advantages of the SB PRO**

- Available in 6 and 9 litre versions
- Tried-and-tested GLORIA strike-knob activation.
- Robust handle made of glass-fibre reinforced plastic with ergonomic carrying properties.
- Laser-welded pressure cylinder.
- Exterior coated with durable polyester resin powder coating.
- Long-lasting plastic inner coating to protect against corrosion.
- Approved according to Pressure Equipment Directive 2014/68/EU (CE).
- Uniform, high-strength, glass-fibre reinforced special plastic valve body.
- High temperature, ozone and UV resistant.
- In addition, high chemical resistance, moisture-resistant and corrosion-free.
- Uniform neck ring, thread size M74x2.
- Uniform, black anodised metal locking collar
- Internal propellant bottle with stainless steel adapter and corrosion-resistant plastic coating. (technical data marked with resistant laser printing)
- Ageing-resistant, LABS-free quality hose assembly with fabric insert made of synthetic rubber material.
- Rotatable and stoppable extinguishing pistol for ideal fire fighting.
- Robust, impact-resistant plastic skirt with hose nozzle bracket ensures stability and protection of the unit against damage and corrosion.
- Special foam pipe with high area coverage enables optimum application of the extinguishing agent.

■ **Details and features of the SB PRO**

- High extinguishing performance on B-fire with only 6 litres capacity
- GLORIA foam with impregnating effect on the source of the fire and surroundings
- Special foam nozzle with high surface coverage enables optimum application of the extinguishing agent
- Reignition is largely suppressed.
- Areas of application:

Type	Art.-No.	Extinguishing agent	Model	Propellant	Extinguishing Performance LE*	Discharge range /-time	Temperature range	Total weight	H/W/D in bracket ø – cylinder
SB 6 PRO	813731.0000	Premix	S 6 H	N ₂	21A 183B 6 12	ca. 4,5 m ca. 70 Sec.	+5 °C to +60 °C	ca. 10,1 kg	ca. 550/280/165 mm ø 150 mm
SB 9 PRO	813741.0000	Premix	S 9 H	N ₂	27A 183B 9 12	ca. 4,5 m ca. 90 Sec.	+5 °C to +60 °C	ca. 15,3 kg	ca. 585/280/205 mm ø 190 mm

* extinguishing agent units. If fire extinguishers are provided for both fire classes A+B, the lower LE value applies for the calculation.