

GLORIA®

Safety First

Foam Fire Extinguisher SD 6/9 F



GLORIA®

**FEUERLÖSCHER
FIRE EXTINGUISHER
EXTINCTEUR
EXTINTOR DE INCENDIOS**

6 l Schaum / Foam (Spray)
Eau pulvérisée avec additif / Espuma

21 A 113 B

1. ⓐ Sicherheitsstift herausziehen
ⓑ Remove safety pin.
ⓒ Tirer la goupille de sécurité.
ⓓ Quitar el pasador de seguridad.
2. ⓐ Schlauch fassen.
ⓑ Prendre le flexible.
ⓒ Tomar la manguera.
3. ⓐ Taste niederdrücken.
ⓑ Press handle.
ⓒ Apretar la palanca.

Vorsicht bei elektrischen Anlagen!
Nur bis 1000 V; Mindestabstand 1 m.
Attention in presence of electricity!
Only up to 1000 V; min. distance 1 meter.
Attention en présence d'électricité!
Utilisable sur tension inférieure à 1000 V.
Tenir le diffuseur à plus de 1 m.
¡Precaución en presencia de electricidad!
Solo hasta 1000 V; distancia mínima: 1 m.

Hersteller / Manufacturer: Diestedder Str. 39 • D-59329 Wadersloh
Tel. +49 (0) 25 23 79349-900
www.gloria.de

GLORIA GmbH

GLORIA®

**FEUERLÖSCHER
FIRE EXTINGUISHER
EXTINCTEUR
EXTINTOR DE INCENDIOS**

6 l Schaum / Foam (Spray)
Eau pulvérisée avec additif / Espuma

21 A 113 B

1. ⓐ Sicherheitsstift herausziehen.
ⓑ Remove safety pin.
ⓒ Tirer la goupille de sécurité.
ⓓ Quitar el pasador de seguridad.
2. ⓐ Schlauch fassen.
ⓑ Take hose.
ⓒ Prendre le flexible.
ⓓ Tomar la manguera.
3. ⓐ Taste niederdrücken.
ⓑ Press handle.
ⓒ Apretar la palanca.

Vorsicht bei elektrischen Anlagen!
Nur bis 1000 V; Mindestabstand 1 m.
Attention in presence of electricity!
Only up to 1000 V; min. distance 1 meter.
Attention en présence d'électricité!
Utilisable sur tension inférieure à 1000 V.
Tenir le diffuseur à plus de 1 m.
¡Precaución en presencia de electricidad!
Solo hasta 1000 V; distancia mínima: 1 m.






Hersteller / Manufacturer: Diestedder Str. 39 • D-59329 Wadersloh
Tel. +49 (0) 25 23 79349-900
www.gloria.de




GLORIA GmbH

■ Main advantages of the SD 6/9 F

- Available in 6 l and 9 l version
- Ready for immediate use after the safety pin is pulled out
- Practical devices of standard class of high extinguishing performance
- Easy to use squeeze-grip operation - for carrying and releasing at the same time
- Extinguishing agent made of high-quality steel
- Hose assembly resistant to aging

■ Details and performance features of the SD 6/9 F

- Frost-resistant to -20 °C
- Foam with impregnating effect on the source of the fire and surroundings
- Special foam nozzle with high surface coverage enables optimum application of the extinguishing agent
- Reignition is largely suppressed.
- Areas of application:     

Type	Art.-No.	Extinguishing agent	Model	Propellant	Performance LE*	Discharge time/-range	Temperature range	Total weight	H/W/D in bracket ø - cylinder
 SD 6 F	814201.0000	Premix	S 6 L	N ₂	21A 113B 6 6	ca. 4 m ca. 35 Sec.	-20 °C to +60 °C	ca. 10,9 kg	ca. 540/275/182 mm ø 170 mm
  SD 9 F	814211.0000	Premix	S 9 L	N ₂	27A 183B 9 12	ca. 4 m ca. 48 Sec.	-20 °C to +60 °C	ca. 15,1 kg	ca. 617/300/202 mm ø 190 mm

Extinguishing agent units. If fire extinguishers are intended for both fire classes A+B, the lower LE value applies for the calculation