

# GLORIA®

Safety First

## Powder fire extinguisher PH 9 STAR



**■ Main advantages of the PH STAR**

- Intuitive and ready to use in no time: unlock, lift the handle – done!
- Robust carrying handle made of glass-fibre reinforced plastic with ergonomic carrying characteristics.
- Laser-welded pressurised cylinder.
- Exterior coated with durable polyester resin powder coating.
- Long-lasting plastic inner coating to protect against corrosion.
- Approved in accordance with the Pressure Equipment Directive 2014/68/EU (CE).
- Uniform, high-strength, glass fibre-reinforced special plastic valve body.
- High temperature, ozone and UV resistant.
- Also highly resistant to chemicals, moisture and corrosion.
- Standardised neck ring, thread size M74x2.
- Uniform, black anodised metal locking collar.
- Internal propellant bottle with stainless steel adapter and corrosion-resistant plastic coating. (technical data marked with resistant laser printing)
- Ageing-resistant, LABS-free quality hose assembly with fabric insert made of synthetic rubber material.
- Swivelling and adjustable extinguishing pistol for optimum fire fighting.
- Robust, impact-resistant plastic base ring with hose nozzle bracket ensures stability and protects the device against damage and corrosion.
- Special foam tube with high surface coverage enables optimum application of the extinguishing agent.

**■ Details and performance features of the PH STAR**

- Environmentally friendly, performance-differentiated quality ABC extinguishing powder
- Nearly universal application
- Immediate, fast extinguishing due to the effect of cooling and suppression, enriched with an anti-catalytic effect
- Reignition of solid fires is prevented
- Gray colour code indicates extinguishing powder
- GLORIA extinguishing powders are hydrophobic and non-toxic
- GLORIA extinguishing powders with excellent quality and durability
- Areas of application:

Type	Art.-No.	Extinguishing agent	Model	Agent	Performance LE*	Spraying range/-duration	Temperature range	Total weight	H/W/D in bracket ø - cylinder
<b>PH 9 STAR</b>	800641.0000	ABC powder	PG 9 H	CO <sub>2</sub>	55A 233B C 15 15	ca. 7 m ca. 23 Sec.	-30 °C to +60 °C	ca. 14,3 kg	ca. 555/290/185 mm ø 170 mm

\* extinguishing agent units. If fire extinguishers are provided for both fire classes A+B, the lower LE value applies for the calculation.