

GLORIA®

Safety First





Foam Fire Extinguisher SK 50 S




■ Main Advantages of SK 50 S

- Certified according to EN 1866
- Designed for practical use by one person
- Space-saving accommodation of the hose assembly around the extinguishing agent container
- Rotatable and adjustable extinguishing pistol enables targeted fire fighting
- Extinguishing agent container completely made of “stainless” steel
- Tilt-proof due to optimal center of gravity
- Film-forming extinguishing agent, especially suitable for liquid fires

■ Details and Features of SK 50 S

- Environmentally friendly, easy-to-maintain piston cartouche
- With steering control for maximum manoeuvrability, even at hard-to-reach sources of fire
- Separate storage of foam concentrate and water thanks to patented piston cartouche
- Environmentally friendly maintenance and easy refilling of the extinguisher
- The mobile fire extinguisher can be reused when refilling
- Long-lasting foam concentrate with consistently high extinguishing performance
- 100% mixing of the extinguishing agent thanks to the piston principle, even with high viscosity
- with marine approval (MED)
- Pressure content product less than 1000, therefore no ZÜS test required
- Suitable for use on electrical installations up to 1000 volts / minimum distance 1 m
- Areas of Use:    

Type	Art.-No.	Extinguishing Agent	Model	Propellant	Extinguishing Performance LE*	Discharge range / time	Temperature Range	Total weight	H/W/D in bracket ø – cylinder
 SK 50 S	5 m: 810868.2969 10 m: 810869.2969	Foam concentrate + Water	S 50 H	N ₂	IV B 50	ca. 8 m ca. 300 Sec.	5 °C to +60 °C	ca. 84 kg	ca. 1050/565/675 mm ø 400 mm

*LE = If fire extinguishers are intended for both fire classes A+B, the lower extinguishing agent unit value applies for the calculation.