

GLORIA®

Safety First




Water Fire Extinguisher W 6/9 EASY





■ Main advantages of the W 6/9 EASY

- Large performance portfolio within the extinguishing agent water (6 and 9 l)
- Consistently used uniform operating elements
- Good carrying characteristics due to stable squeeze-grip operation
- Uniform, high-strength, glass-fibre reinforced special plastic valve body. Also robust, tensile strength, stable, high chemical resistance, moisture-resistant, corrosion-free, high temperature resistance, UV-resistant.
- All valve components with standardised neck rings
- Uniform neck ring M 74
- Uniform, black anodised metal locking collar
- Ageing resistant hose assembly

■ Details and performance features of the W 6/9 EASY

- 6 and 9 l water extinguishers with pure water without any additives (type W)
- Blue color code indicates water as the extinguishing agent
- Areas of application:   

Type	Art.-No.	Extinguishing agent	Model	Propellant	Extinguishing Performance LE	Discharge range /time	Temperature Range	Total weight	H/W/D in bracket ø – cylinder
 W 6 EASY	801601.0000	Water	W 6 H	CO ₂	21A 6	ca. 4 m ca. 32 Sec.	+5 °C to +60 °C	ca. 10,0 kg	ca. 600/310/165 mm 150 mm
 W 9 EASY	801611.0000	Water	W 9 H	CO ₂	27A 9	ca. 4 m ca. 39 Sec.	+5 °C to +60 °C	ca. 15,2 kg	ca. 620/290/205 mm 190 mm

Extinguishing agent units. If fire extinguishers are intended for both fire classes A+B, the lower LE value applies for the calculation.