

GLORIA®

Safety First

Water Fire Extinguisher WD 9




■ **Main advantages of the WD 9**

- Ready for immediate use after the safety pin is pulled out
- Practical devices of standard class of high extinguishing performance
- Easy to use squeeze-grip operation – for carrying and releasing at the same time
- Extinguishing agent container made of high-quality steel
- Hose assembly resistant to aging

■ **Details and performance characteristics of the WD 9** 

- External weather-resistant and durable coating
- Holder for extinguishing nozzle integrated into skirt
- Durable brass fitting with integrated test valve
- With wall bracket
- Suitable for electrical installations up to 1000 volts at a minimum distance of 1 m
- With wall bracket as standard
- Optionally available with matching car bracket

- Areas of application: 

Type	Art.-No.	Extinguishing agent	Model	Propellant	Extinguishing capacity	Discharge time/-range	Temperature range	Total weight	H/W/D in holder ø – Container
 WD 9	801671.0000	Water + Additive	W-9-L	N ₂	21A 6	ca. 4 m ca. 97 Sec.	5 °C to +60 °C	ca. 14,2 kg	ca. 522/300/205 mm 190 mm

* Extinguishing agent units. If fire extinguishers are intended for both fire classes A+B, the lower LE value applies for the calculation.