

GLORIA®

Safety First

Water Fire Extinguisher WDPF 9



GLORIA

Safety First

GLORIA GmbH | Diestedder Straße 39 | 59329 Wadersloh
Telefon +49 (0)2523 79349-900 | Telefax +49 (0)2523 79349-93
info@gloria.de | www.gloria.de

■ **Main advantages of the WDPF 9**

- Ready for immediate use after the safety pin is pulled out
- Practical devices of standard class of high extinguishing performance
- Easy to use squeeze-grip operation – for carrying and releasing at the same time
- Extinguishing agent container made of high-quality steel
- Hose assembly resistant to aging

■ **Details and performance characteristics of the WDPF 9**

- External weather-resistant and durable coating
- Holder for extinguishing nozzle integrated into skirt
- Durable brass fitting with integrated test valve
- With wall bracket
- Suitable for electrical installations up to 1000 volts at a minimum distance of 1 m
- With wall bracket as standard
- Optionally available with matching car bracket
- Frost-proof to -30 °C
- Areas of application:

Type	Art.-No.	Extinguishing agent	Model	Propellant	Extinguishing capacity	Discharge time/-range	Temperature range	Total weight	H/W/D in holder ø – Container
WDPF 9	801661.0000	Water + antifreeze	W-9-L	N ₂	21A 6	ca. 4 m ca. 63 Sec.	-30 °C to +60 °C	ca. 16,3 kg	ca. 610/310/205 mm 190 mm

* Extinguishing agent units. If fire extinguishers are intended for both fire classes A+B, the lower LE value applies for the calculation.