

GLORIA®

Safety First

Water Fire Extinguisher WH 6/9 STAR



■ **Main Advantages of WH STAR**

- Available in 6 l and 9 l version
- Intuitive and therefore ready to use in a flash: unlock, simply lift the handle—done!
- Robust carrying handle made of glass fiber reinforced plastic with ergonomic carrying properties.
- Laser-welded pressure vessel.
- Exterior with durable polyester resin powder coating.
- Durable plastic inner coating for protection against corrosion.
- Approved in accordance with Pressure Equipment Directive 2014/68/EU (CE).
- Uniform, high-strength, glass fiber reinforced special plastic valve body.
- High temperature, ozone and UV resistant.
- In addition, high chemical resistance, moisture resistant, and corrosion-free.
- Uniform thread size, thread size M74x2.
- Uniform, black anodized metal cap nut.
- Internal propellant bottle with stainless steel adapter and corrosion-resistant plastic coating. (Technical data marked with durable laser printing)
- Aging-resistant, LABS-free, high-quality hose with synthetic rubber fabric reinforcement.
- Rotatable and adjustable fire extinguisher for optimal firefighting.
- Robust, impact-resistant plastic base ring with hose nozzle holder ensures stability and protects the device against damage and corrosion.
- Special foam pipe with high surface coverage enables optimal application of the extinguishing agent.
- Robust, impact-resistant plastic base ring with hose nozzle holder ensures stability and protects the device against damage and corrosion.

■ **Details and performance features of the WH STAR**

- Water extinguishers with top ratings: Type WH 9 with 12 LE – and environmentally friendly too
- Blue color code on the label indicates: Water as extinguishing agent
- Areas of application:

| Type | Art.-No. | Extinguishing agent | Model | Propellant | Performance LE* | Discharge time/-range | Temperature range | Total weight | H/W/D in bracket ø - cylinder |
|------------------|-------------|---------------------|-------|-----------------|-----------------|------------------------|-------------------|--------------|----------------------------------|
| WH 6 STAR | 803821.0000 | Wasser + Additive | W 6 H | CO ₂ | 34A 10 | ca. 5 m ca. 74 Sec. | 0 °C to +60 °C | ca. 10,3 kg | ca. 540/280/165 mm ø 150 mm |
| WH 9 STAR | 803831.0000 | Wasser + Additive | W 9 H | CO ₂ | 43A 12 | ca. 5 m ca. 93 Sec. | 0 °C to +60 °C | ca. 15,5 kg | ca. 575/280/205 mm ø 190 mm |

Extinguishing agent units. If fire extinguishers are intended for both fire classes A+B, the lower LE value applies for the calculation.