

# GLORIA®

Safety First

## Water Fire Extinguisher WH 6/9 EASY



GLORIA




Safety First



GLORIA GmbH | Diestedder Straße 39 | 59329 Wadersloh  
Telefon +49 (0)2523 79349-900 | Telefax +49 (0)2523 79349-93  
info@gloria.de | www.gloria.de

### ■ Main advantages of the WH 6/9 EASY

- Large performance portfolio within the extinguishing agents foam (6 and 9 l), water (6 and 9 l), fat fire (3 and 6 l) and powder (6, 9 and 12 kg)
- Consistently used uniform operating elements
- Good carrying characteristics due to stable squeeze-grip operation
- Uniform, high-strength, glass-fibre reinforced special plastic valve body. Also robust, tensile strength, stable, high chemical resistance, moisture-resistant, corrosion-free, high temperature resistance, UV-resistant.
- All valve components with standardised neck rings
- Uniform neck ring M 74
- Uniform, black anodised metal locking collar
- Ageing resistant hose assembly

### ■ Details und Leistungsmerkmale des WH 6/9 EASY

- Water extinguisher of the best parameters: Type WH with 12 LE and 9 l capacity – and environmentally friendly
- 6 and 9 litre water extinguishers with pure water without additives (Type W)
- Frost-proof versions (-30°) with 6 and 9 litre capacity available (Type WF)
- Blue colour code indicates water extinguishing agent
- Areas of application:   

Type	Art.-No.	Extinguishing agent	Model	Propellant	Extinguishing Performance LE	Discharge range /time	Temperature Range	Total weight	H/W/D in bracket ø – cylinder
 WH 6 EASY	801601.1776	Water + Additive	W 6 H	CO <sub>2</sub>	34A 10	ca. 5 m ca. 60 Sec.	0 °C to +60 °C	ca. 10,2 kg	ca. 600/310/165 mm 150 mm
 WH 9 EASY	801611.1776	Water + Additive	W 9 H	CO <sub>2</sub>	43A 12	ca. 5 m ca. 70 Sec.	0 °C to +60 °C	ca. 15,4 kg	ca. 620/290/205 mm 190 mm

Extinguishing agent units. If fire extinguishers are intended for both fire classes A+B, the lower LE value applies for the calculation.