



Safety First

Water Fire Extinguisher WH 6/9 PRO



■ **Main advantages of the WH 6/9 PRO**

- Tried-and-tested GLORIA strike-knob activation.
- Robust handle made of glass-fibre reinforced plastic with ergonomic carrying properties.
- Laser-welded pressure cylinder.
- Exterior coated with durable polyester resin powder coating.
- Long-lasting plastic inner coating to protect against corrosion.
- Approved according to Pressure Equipment Directive 2014/68/EU (CE).
- Uniform, high-strength, glass-fibre reinforced special plastic valve body.
- High temperature, ozone and UV resistant.
- In addition, high chemical resistance, moisture-resistant and corrosion-free.
- Uniform neck ring, thread size M74x2.
- Uniform, black anodised metal locking collar
- Internal propellant bottle with stainless steel adapter and corrosion-resistant plastic coating. (technical data marked with resistant laser printing)
- Ageing-resistant, LABS-free quality hose assembly with fabric insert made of synthetic rubber material.
- Rotatable and stoppable extinguishing pistol for ideal fire fighting.
- Robust, impact-resistant plastic skirt with hose nozzle bracket ensures stability and protection of the unit against damage and corrosion.
- Special foam pipe with high area coverage enables optimum application of the extinguishing agent.

■ **Details and performance characteristics of the WH 6/9 PRO**

- Water extinguisher of the best parameters: Type WH 9 with 12 LE – and environmentally friendly
- The blue colour code indicates a water extinguishing agent
- Hose connection and diptube made of stainless steel
- Areas of application:

Type	Art.-No.	Extinguishing agent	Model	Propellant	Extinguishing capacity LE*	Discharge time/-range	Temperature range	Total weight	H/W/D in holder ø – Container
WH 6 PRO	803801.0000	Water + Additive	W 6 H	CO ₂	34A 10	ca. 5 m ca. 74 Sec.	0 °C to +60 °C	ca. 10,3 kg	ca. 550/280/165 mm ø 150 mm
WH 9 PRO	803811.0000	Water + Additive	W 6 H	CO ₂	43A 12	ca. 5 m ca. 90 Sec.	0 °C to +60 °C	ca. 15,5 kg	ca. 585/280/205 mm ø 190 mm

* Extinguishing agent units. If fire extinguishers are intended for both fire classes A+B, the lower LE value applies for the calculation.