

GLORIA®

Safety First

Water Fire Extinguisher WKL 6/9 PRO



■ **Main advantages of the WKL 6/9 PRO**

- Tried-and-tested GLORIA strike-knob activation.
- Robust handle made of glass-fibre reinforced plastic with ergonomic carrying properties.
- Laser-welded pressure cylinder.
- Exterior coated with durable polyester resin powder coating.
- Long-lasting plastic inner coating to protect against corrosion.
- Approved according to Pressure Equipment Directive 2014/68/EU (CE).
- Uniform, high-strength, glass-fibre reinforced special plastic valve body.
- High temperature, ozone and UV resistant.
- In addition, high chemical resistance, moisture-resistant and corrosion-free.
- Uniform neck ring, thread size M74x2.
- Uniform, black anodised metal locking collar
- Internal propellant bottle with stainless steel adapter and corrosion-resistant plastic coating. (technical data marked with resistant laser printing)
- Ageing-resistant, LABS-free quality hose assembly with fabric insert made of synthetic rubber material.
- Rotatable and stoppable extinguishing pistol for ideal fire fighting.
- Robust, impact-resistant plastic skirt with hose nozzle bracket ensures stability and protection of the unit against damage and corrosion.
- Special foam pipe with high area coverage enables optimum application of the extinguishing agent.

■ **Details and performance features of the WKL 6/9 PRO**

- Fluorine-free extinguishing agent concentrate, without environmentally harmful PFOS or PFOA
- Deliberate avoidance of extinguishing substances in the water
- Blue colour code indicates water as extinguishing agent
- Extinguishing lance for additional distance to the source of danger at 4m spray range
- High ease of maintenance thanks to cartridge technology
- Specially designed for lithium-ion batteries up to 642Wh** (WKL6PRO) or 1285Wh** (WKL 9 PRO), with pouches up to 700Wh (WKL 9 PRO)

- Areas of application:

** The tests were carried out on cell Type 18650. The suitability test on lithium-ion batteries was carried out by the Dutch institute KIWA!

Type	Art.-No.	Extinguishing agent	Model	propellant	Performance LE*	Spraying range/-duration	Temperature range	Total weight	H/W/D in bracket ø - cylinder
WKL 6 PRO	803841.0000	Concentrate in cartridge + water	W 6 H	CO ₂	21A 6	ca. 4 m ca. 65 Sec.	+5 °C to +60 °C	ca. 10,5 kg	ca. 630/216/165 mm ø 150 mm
WKL 9 PRO	803851.0000	Concentrate in cartridge + water	W 6 H	CO ₂	27A 9	ca. 4 m ca. 80 Sec.	+5 °C to +60 °C	ca. 15,6 kg	ca. 640/480/205 mm ø 190 mm

Extinguishing agent units. If fire extinguishers are intended for both fire classes A+B, the lower LE value applies for the calculation.