



Safety First

Powder Fire Extinguisher P 2 GM . P 2 G . P 1 GM



■ Main advantages of the P 2 GM . P 2 G . P 1 GM

- Compact devices of the standard class with high extinguishing performance
- Comfortable operation with one hand or easy activation with a lever – used both for carrying and activation
- High-quality pressure vessels made of high-strength aluminum or steel
- Extinguishing agent jet can be turned off at any time
- Devices can be tested and refilled

■ Details and performance characteristics of the P 2 GM . P 2 G . P 1 GM

- External weather-resistant and durable coating 100% polyester resin coating (heavy metal-free) for a long service life
- Smallest external dimensions thanks to special valve and container design
- Valve body made of high-strength materials
- Rounded edges in accordance with automotive industry specifications
- Convenient one-handed operation (safety release and triggering possible with one hand)
- Areas of application:  

Type	Art.-No.	Extinguishing Agent	Model	Propellant	Extinguishing Performance LE*		Discharge range / time	Temperature Range	Total weight	H/W/D in bracket ø – cylinder
 P 2 GM	001473.0000	ABC-Powder	PG 2 L	N ₂	13A 4	89B C 5	ca. 4 m ca. 15 Sec.	-30 °C to +60 °C	ca. 3,5 kg	ca. 322/111/145 mm ø 110 mm
 P 2 G	001463.0000	ABC-Powder	PG 2 L	N ₂	13A 4	89B C 5	ca. 4 m ca. 15 Sec.	-30 °C to +60 °C	ca. 3,5 kg	ca. 322/111/145 mm ø 110 mm
P 1 GM	001443.0000	ABC-Powder	PG 1 L	N ₂	8A 2	34B C 2	ca. 4 m ca. 9 Sec.	-30 °C to +60 °C	ca. 2,1 kg	ca. 270/95/120 mm ø 90 mm

*Extinguishing agent units. If fire extinguishers are intended for both fire classes A+B, the lower LE value applies for the calculation. **With pressure gauge as standard.  MED License