

GLORIA®

Safety First

Powder fire extinguisher P 50 G . P 50 SV . P 50 M



GLORIA

Safety First

GLORIA GmbH | Diestedder Straße 39 | 59329 Wadersloh
Telefon +49 (0)2523 79349-900 | Telefax +49 (0)2523 79349-93
info@gloria.de | www.gloria.de

■ Main Advantages of P 50 G . P 50 SV . P 50

- Tested in accordance with EN 1866
- Designed for practical use by one person
- Space-saving storage of the hose line around the extinguishing agent container
- Tilt-proof thanks to optimal/favorable center of gravity
- Rotatable and adjustable extinguishing gun enables targeted firefighting

■ Details and Features of P 50 G . P 50 SV . P 50 M

- Exterior with weather-resistant and durable coating
- Large wheels (30 cm), ideal for uneven terrain
- Depending on the model, either a 5 m or 10 m high-pressure hose for flexible use
- Pressure content product less than 1000, therefore no ZÜS testing necessary
- Safe storage of N₂ propellant powder in the retaining bracket
- Built-in safety valve in the shut-off valve
- Large, easy-to-maintain filling opening
- With steering control for maximum maneuverability, even at hard-to-reach sources of fire
- Type P 50 G with maritime approval (MED)
- Throw height approx. 10 m (Type P 50 G)
- Type P 50 SV with high-quality potassium sulfate powder, suitable for combined use with foam, with maritime approval
- Type P 50 M with applicator tube for metal fires and 10 m hose
- Areas of application:

Type	Art.-No.	Extinguishing Agent	Model	Propellant	Extinguishing Performance LE*	Discharge range / time	Temperature Range	Total weight	H/W/D in bracket ø – cylinder
P 50 G	5 m:000901.2969 10 m:000906.2969	ABC-Powder	PG 50 H	N ₂	IV B 60	ca. 11 m ca. 90 Sec.	-30 °C to +60 °C	ca. 82 kg	ca. 1070/475/560 mm ø 300 mm
P 50 SV	5m:000901.2975 10m:000906.2975	BC-Powder	P 50 H	N ₂	IV B 60	ca. 10-12 m ca. 240 Sec.	-30 °C to +60 °C	ca. 82 kg	ca. 1070/475/560 mm ø 300 mm
P 50 M	10m:000907.2976	Metal Fire Powder	PM 50 H	N ₂	D	Streu. ca.90 Sec.	-30 °C to +60 °C	ca. 82 kg	ca. 1070/475/560 mm ø 300 mm

*LE = If fire extinguishers are intended for both fire classes A+B, the lower extinguishing agent unit value applies for the calculation.

MED License