



Saftey First

Powder Fire Extinguisher PDE 1 GA . PD 2 GA



■ Main advantages of the PD 2 GA . PDE 1 GA

- Compact standard-class devices with high extinguishing performance
- One-handed comfort operation or easy-to-use hand lever release — for carrying and releasing at the same time
- High-quality pressure vessels made of high-strength aluminum or steel
- Extinguishing agent jet can be turned off at any time
- Devices can be tested and refilled

■ Details and performance characteristics of the PD 2 GA . PDE 1 GA

- Exterior with weather-resistant, durable, 100% polyester resin coating (free of heavy metals) for a long service life
- Minimal external dimensions thanks to special valve and container design
- Valve body made of high-strength materials
- Carrying handle with operating lever made of sheet steel, painted red
- With pressure gauge
- Simple squeeze-grip operation
- Areas of application:  

Type	Art.-No.	Extinguishing Agent	Model	Propellant	Extinguishing Performance LE*		Discharge range / time	Temperature Range	Total weight	H/W/D in bracket ø – cylinder
 PD 2 GA**	001493.0000	ABC-Powder	PG 2 L	N ₂	13A 4	70B C 4	ca. 4 m ca. 9 Sec.	-30 °C to +60 °C	ca. 3,4 kg	ca. 330/115/155 mm ø 110 mm
PDE 1 GA**	001393.0000	ABC-Powder	PG 1 L	N ₂	8A 2	34B C 2	ca. 4 m ca. 9 Sec.	-30 °C to +60 °C	ca. 2,1 kg	ca. 280/93/135 mm ø 90 mm

* Extinguishing agent units. If fire extinguishers are intended for both fire classes A+B, the lower LE value applies for the calculation.**With pressure gauge as standard.  MED License