

GLORIA®

Safety First

Powder fire extinguisher PEF 50 . PEF 100



GLORIA

Safety First

GLORIA GmbH | Diestedder Straße 39 | 59329 Wadersloh
Telefon +49 (0)2523 79349-900 | Telefax +49 (0)2523 79349-93
info@gloria.de | www.gloria.de

■ Main Advantages of PEF 50 . PEF 100

- Tested in accordance with EN 1866
- Designed for practical use by one person
- Space-saving storage of the hose line around the extinguishing agent container
- Tilt-proof thanks to optimal/favorable center of gravity
- Rotatable and adjustable extinguishing gun enables targeted firefighting

■ Details and Features of PEF 50. PEF 100

- Exterior with weather-resistant and durable coating
- Large wheels (30 cm), ideal for uneven terrain
- Depending on the model, either a 5 m or 10 m high-pressure hose for flexible use
- Pressure content product less than 1000, therefore no ZÜS inspection necessary (PEF 50)
- Parkable attack device, throw height approx. 5 m
- With maritime approval (MED)
- Areas of application: 

Type	Art.-No.	Extinguishing Agent	Model	Propellant	Extinguishing Performance LE*	Discharge range / time	Temperature Range	Total weight	H/W/D in bracket ø – cylinder
 PEF 50	5 m:000900.2851 10 m:000906.2851	ABC-Powder	PG 50 H	N ₂	IV B 60**	ca. 6 m ca. 40 Sec.	-30 °C to +60 °C	ca. 84 kg	ca. 1050/465/550 mm ø 300 mm
 PEF 100	10m:000820.2851	ABC-Powder	PG 100 H	N ₂	IV B 125**	ca. 10-12 m ca. 75 Sec.	-30 °C to +60 °C	ca. 120 kg	ca. 1290/550/770 mm ø 300

*LE = If fire extinguishers are intended for both fire classes A+B, the lower extinguishing agent unit value applies for the calculation.

**Calculation based on type PEF 50.  MED License