

GLORIA®

Safety First

Powder Fire Extinguisher P 6/12 G



GLORIA

Safety First

GLORIA GmbH | Diestedder Straße 39 | 59329 Wadersloh
Telefon +49 (0)2523 79349-900 | Telefax +49 (0)2523 79349-93
info@gloria.de | www.gloria.de

■ Main advantages of the P 6/12 G

- Immediately ready for use after opening the CO₂ propellant bottle.
- Rotatable and stoppable extinguishing pistol for ideal fire fighting.
- Top quality pressure propellant vessels made of high strength steel

■ Details and performance features of the P 6/12 G

- External weather-resistant and durable coating 100% polyester resin coating (free of heavy metals) for long service life
- External TÜV-tested CO₂ propellant bottle with safety burst disc device
- Metal valve with integrated safety valve
- A solid plastic skirt protects the container against damage and ensures high stability
- Very maintenance-friendly design
- Integrated hose and propellant bottle holder on the skirt
- Areas of application: 



Carrying handle

Type	Art.-No.	Extinguishing agent	Model	Propellant	Performance LE*	Discharge time/-range	Temperature range	Total weight	H/W/D in bracket ø - cylinder
P 6 G	000621.2046	ABC-Powder	PG 6 H	CO ₂	43 A 233 B C 12 15	5 m ca. 22 Sec.	-30 °C to +60 °C	11,0 kg	480/340/150 mm ø 150 mm
P 12 G	000671.2046	ABC-Powder	PG 12 H	CO ₂	55 A 233 B C 15 15	7 m ca. 34 Sec.	-30 °C to +60 °C	20,0 kg	560/370/190 mm ø 190 mm

* Extinguishing agent units. If fire extinguishers are intended for both fire classes A+B, the lower LE value applies for the calculation. | **with pressure gauge