

GLORIA®

Safety First

Powder fire extinguisher PX 6 STAR



GLORIA®

Safety First

GLORIA GmbH | Diestedder Straße 39 | 59329 Wadersloh
Telefon +49 (0)2523 79349-900 | Telefax +49 (0)2523 79349-93
info@gloria.de | www.gloria.de

■ Main advantages of the PX STAR

- Available in 6 kg version
- Intuitive and ready to use in no time: unlock, lift the handle – done!
- Robust carrying handle made of glass-fibre reinforced plastic with ergonomic carrying characteristics.
- Laser-welded pressurised cylinder.
- Exterior coated with durable polyester resin powder coating.
- Long-lasting plastic inner coating to protect against corrosion.
- Approved in accordance with the Pressure Equipment Directive 2014/68/EU (CE).
- Uniform, high-strength, glass fibre-reinforced special plastic valve body.
- High temperature, ozone and UV resistant.
- Also highly resistant to chemicals, moisture and corrosion.
- Standardised neck ring, thread size M74x2.
- Uniform, black anodised metal locking collar.
- Internal propellant bottle with stainless steel adapter and corrosion-resistant plastic coating. (technical data marked with resistant laser printing)
- Ageing-resistant, LABS-free quality hose assembly with fabric insert made of synthetic rubber material.
- Swivelling and adjustable extinguishing pistol for optimum fire fighting.
- Robust, impact-resistant plastic base ring with hose nozzle bracket ensures stability and protects the device against damage and corrosion.
- Special foam tube with high surface coverage enables optimum application of the extinguishing agent.

■ Details and performance features of the PH STAR

- Type PX 6 STAR as a high-performance device with 15 LE environmentally friendly, performance-differentiated quality ABC extinguishing powder
- Nearly universal application
- Immediate, fast extinguishing due to the effect of cooling and suppression, enriched with an anti-catalytic effect
- Reignition of solid fires is prevented
- Gray colour code indicates extinguishing powder
- GLORIA extinguishing powders are hydrophobic and non-toxic
- GLORIA extinguishing powders with excellent quality and durability
- Areas of application: 

Type	Art.-No.	Extinguishing agent	Model	Agent	Performance LE*	Spraying range/-duration	Temperature range	Total weight	H/W/D in bracket ø - cylinder
PX 6 STAR	800631.3016	High-performance-ABC powder	PG 6 H	CO ₂	55A 233B C 12 15	ca. 6 m ca. 22 Sec.	-30 °C to +60 °C	ca. 9,9 kg	ca. 500/300/165 mm ø 150 mm

* extinguishing agent units. If fire extinguishers are provided for both fire classes A+B, the lower LE value applies for the calculation.