

GLORIA®

Safety First

Water Fire Extinguisher W 6/9 STAR



GLORIA

Safety First

GLORIA GmbH | Diestedder Straße 39 | 59329 Wadersloh
Telefon +49 (0)2523 79349-900 | Telefax +49 (0)2523 79349-93
info@gloria.de | www.gloria.de

■ Main Advantages of W STAR

- Available in 6 l and 9 l version
- Intuitive and therefore ready to use in a flash: unlock, simply lift the handle—done!
- Robust carrying handle made of glass fiber reinforced plastic with ergonomic carrying properties.
- Laser-welded pressure vessel.
- Exterior with durable polyester resin powder coating.
- Durable plastic inner coating for protection against corrosion.
- Approved in accordance with Pressure Equipment Directive 2014/68/EU (CE).
- Uniform, high-strength, glass fiber reinforced special plastic valve body.
- High temperature, ozone and UV resistant.
- In addition, high chemical resistance, moisture resistant, and corrosion-free.
- Uniform thread size, thread size M74x2.
- Uniform, black anodized metal cap nut.
- Internal propellant bottle with stainless steel adapter and corrosion-resistant plastic coating. (Technical data marked with durable laser printing)
- Aging-resistant, LABS-free, high-quality hose with synthetic rubber fabric reinforcement.
- Rotatable and adjustable fire extinguisher for optimal firefighting.
- Robust, impact-resistant plastic base ring with hose nozzle holder ensures stability and protects the device against damage and corrosion.
- Special foam pipe with high surface coverage enables optimal application of the extinguishing agent.
- Robust, impact-resistant plastic base ring with hose nozzle holder ensures stability and protects the device against damage and corrosion.

■ Details and performance features of the W STAR

- Blue color code on the label indicates: Water as extinguishing agent
- Extinguishing lance for additional distance to the source of danger at 4m spray range
- Areas of application:

Type	Art.-No.	Extinguishing agent	Model	Propellant	Performance LE*	Discharge time/-range	Temperature range	Total weight	H/W/D in bracket ø - cylinder
W 6 STAR	803861.0000	Water	W 6 H	CO ₂	21A 6	ca. 4 m ca. 50 Sec.	5 °C to +60 °C	ca. 10,5 kg	ca. 630/216/165 mm ø 150 mm
W 9 STAR	803871.0000	Water	W 6 H	CO ₂	27A 9	ca. 4 m ca. 50 Sec.	5 °C to +60 °C	ca. 15,6 kg	ca. 640/430/205 mm ø 190 mm

Extinguishing agent units. If fire extinguishers are intended for both fire classes A+B, the lower LE value applies for the calculation.