GLORIA®

Safety First

Foam Fire Extinguisher
SEF 50 SF 30



FLUORINE-FREE

A B

GS

bsi. ISO 9001 Quality Management TS 16949 Automotive Quality Management

GLORIA GmbH | Diestedder Straße 39 | 59329 Wadersloh
Telefon +49 (0)2523 79349-900 | Telefax +49 (0)2523 79349-93
info@gloria.de | www.gloria.de

Main Advantages of SEF 50 SF 30

- Certified according to EN 1866
- Designed for practical use by one person
- Space-saving storage of hose assembly around the extinguishing agent container
- Rotatable and adjustable extinguishing pistol enables targeted fire fighting
- Extinguishing agent container completely made of “stainless” steel
- Tilt-proof due to optimal center of gravity
- Film-forming extinguishing agent, especially suitable for liquid fires

Details and Features of SEF 50 SF 30

- Weather-resistant and durable coating on the outside
- Large wheels (30 cm), ideal for uneven surfaces
- 10 m high-pressure hose for flexible use
- Safety valve integrated in the shut-off valve
- Safe storage of the N_2 propellant bottle in the retaining bracket
- Fluorine-free
- MED approval
- Uniform extinguishing gun with foam pipe
- Frost-resistant up to -30 °C
- With extinguishing pistol, suitable for electrical installations up to 1000 Volt / minimum distance 1 m
- Pressure content product less than 1000, no ZÜS testing necessary
- Areas of application:

Type	Art.-No.	Extinguishing Agent	Model	Propellant	Extinguishing Performance LE*	Discharge time	Temperature Range	Total weight	H/W/D ø – cylinder
SEF 50 SF 30	810869.3270	Premix	S 50 L	N_2	A IV B 50	ca. 276 Sec.	-30 °C to +60 °C	ca. 96 kg	ca. 1288/459/645 mm ø 296 mm

**LE = If fire extinguishers are intended for both fire classes A+B, the lower extinguishing agent unit value applies for the calculation.*
MED Certification